

□ PRO

Simple & Flexible Solution

LED FLEXIBLE LINEAR LIGHT

| PRODUCT INFORMATION

- Excellently anti-dust LED strips with professional design to guarantee lighting performance.
- It not only ensure high quality of lighting color consistency but also protect products against from harsh environments.

BENEFITS

- Vivid light color.
- Less maintenance cost and less concerns.

FEATURES

- High CRI>95.
- Operating voltage DC24V.



AREAS OF APPLICATION





Hospitality

Shopping Center





Commercial

Educational Center


I TECHNICAL OPERATING & ELECTRICAL DATA

IP Rating	IP20
Power	10W
LED Quantity	128pcs/meter
Lumen	1030lm/M +/-10%
PCB	Double PCB whole thickness 0.25mm, white color, 10mm, copper thickness 25um x 3pcs (30Z
Chip Size	2.8x3.5x0.8mm
L70	>20000H
Input	DC24V
Maximum Length	5M/Reel
Cutting Unit	Each 16 led is cuttable (cutting space 12.5cm)
Packging	Male & female DC connector, 5m/reel into a anti-static bag, 20 bags into a master carton

SPECIFICATIONS

Code No.	Model No.	Lumen	CRI	CCT
611887	ILS10LVST92250TN01	1030lm	95	2200K/5000K

DIMENSIONS





611887

ACCESSORIES LED FLEXIBLE LINEAR LIGHT CONNECTOR AVAILABLE AS AN ACCESSORY


Code No.	Model No.	IP	Power	Input	Output	Frequency	Dimensions
611946	ILSLVRFDIMMCD01	20	144W	DC24V	DC24V	433.92Hz	40x85x6mm
611948	ILS75W24VCG01	20	75W	AC220-240V	DC24V	50/60Hz	78x110x36mm
611949	ILS100W24VCG01	20	100W	AC220-240V	DC24V	50/60Hz	98x130x41mm
611950	ILS150W24VCG01	20	150W	AC220-240V	DC24V	50/60Hz	98x160x50mm


ACCESSORIES DIMENSIONS






611946 611948





611949 611950

APPLICATION PICTURE



LED FLEXIBLE LINEAR LIGHT

BEYOND LIGHT..
TO THE LAST DETAILS!

