

## Simple & Flexible Solution

### LED FLEXIBLE LINEAR LIGHT

#### PRODUCT INFORMATION

- Excellently waterproof and anti-dust LED strips with professional design to guarantee lighting performance.
- It not only ensure high quality of lighting color consistency but also protect products outdoor against from harsh environments outdoors.

#### **BENEFITS**

- Water proof and vivid light color.
- Less maintenance cost and less concerns on water invasion.

#### **FEATURES**

- High CRI>92.
- Operating voltage DC226V.



#### **AREAS OF APPLICATION**





Hospitality

Shopping Center





Commercial

Educational Center


#### I TECHNICAL OPERATING & ELECTRICAL DATA

IP Rating	IP65, PVC anti-UV
Power	10W/M (for all, each color will be divided accordingly)
LED Quantity	60pcs/meter
Lumen	150lm/M+/-10%
PCB	Single PCB whole thickness 0.15mm, white color, 14mm, copper thickness 25un
Chip Size	5.0x5.0x1.2mm
L70	>20000H
Input	DC226V
Copper Wire	0.15mm x 18pcs
Maximum Length	40M / Reel
Cutting Unit	1 meter
Size	19x8mm
Other Features	Each roll without controller (sold separately)

#### **SPECIFICATIONS**

Code No.	Model No.	Lumen	CRI	ССТ
611851	ILS10HVST930RGB01	150lm	92	RGB/3000K

#### **DIMENSIONS**




611851

# ACCESSORIES LED FLEXIBLE LINEAR LIGHT CONNECTOR AVAILABLE AS AN ACCESSORY


Code No.	Model No.	IP	Power	Input	Output	Frequency	Dimensions
611957	ILSHVSTPCFCH04						21.1x8x1000mm
611939	ILSHVST2H5PC02						L=200mm
611976	ILSHVST2H5PC01						L=300mm
611942	ILSHVRFRGBWCD01	65	361W	DC226V	DC226V	50/60Hz	35x132x33mm
611929	ILS250HVFLLCG02	65	248W	AC220-240V	DC226V	50/60Hz	42x146x33mm
611930	ILS400HVFLLCG02	65	361W	AC220-240V	DC226V	50/60Hz	42x146x33mm

#### **ACCESSORIES DIMENSIONS**



611957 - PVC Profile





611939 - Jumper

611942 - RGBW Controller





#### **APPLICATION PICTURE**



LED FLEXIBLE LINEAR LIGHT BEYOND LIGHT..
TO THE LAST DETAILS!

